

Chiller with air-cooled refrigerating unit and circulation pump. Evaporator (cooler), tank and housing of stainless steel. Pressure-suction pump made of stainless steel. Digital Temperature adjustment and digital temperature display. Level indicator with sight glass.

### MPC-Controller:

Modern and easy to use microprocessor controller with a large temperature display.

Limited to essential functions only:

- \* Large temperature display
- \* LED indicators for pump, cooling and heating
- \* Simple operation using only 3 keys

### Technical data according to DIN 12876

Operating temperature range	-20...40 °C
Temperature adjustment	digital
Temperature indication	digital
Internal temperature sensor	Pt100
Resolution of display	0,1 K
Temperature stability at -10°C	0,2 K
Safety classification	Class I / NFL
Cooling power	
at 15°C	0,6 kW
at 0°C	0,5 kW
at -10°C	0,35 kW
at -20°C	0,15 kW
Refrigeration machine	air-cooled, natural refrigerant
Refrigerant	R290
Refrigerant quantity	0,07 kg
Circulation pump	A
max. delivery	30 l/min
max. delivery pressure	0.7 bar
Pump connection	M16x1 male
min. filling capacity	1,25 l
Volume of expansion	0,7 l
Overall dimensions WxDxH **	280x490x414 mm
Net weight	37 kg
Power supply requirement	230V 1~ 50/60Hz
max. current	3,5 A
Fuse (1 phase)	4 A
min. ambient temperature	5 °C
max. ambient temperature	40 °C



**Order-No.: 3007.0007.99**

**from Serial-No.: 106752 1.2/13**

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions.

Accessories and periphery: Hose coupling nom. dia. 12\*, sleeve nuts thread M16x1\*, cover expansion tank\*, drain valve, connection tubes

\* standard equipment

Output data valid for: Room temperature 20° C

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and + 2% frequency -> not allowed!

-5% voltage and - 2% frequency -> allowed

\*\* Please respect space requirements. See operating conditions at [www.huber-online.com](http://www.huber-online.com)